



DIN 906

Tappi conici con esagono incassato secondo specifiche DIN 906.

Dati espressi in millimetri (mm)

| d | | b | s | t | Peso | |
|---------------------|-----------------------|----------|----------|----------|----------------------------------------------|-------|
| Filettatura metrica | Filettatura Whitworth | | | | | |
| DIN 158 | DIN 3858 | js16 | D12 | min. | kg per 1000 pezzi (7,85 kg/dm ³) | |
| M8 x 1 | - | - | 8 | 4 | 4,0 | 2,1 |
| M10 x 1 | - | R 1/8 | 8 | 5 | 4,0 | 3,4 |
| M12 x 1,5 | - | - | 10 | 6 | 5,0 | 6,10 |
| - | - | R 1/4 | 10 | 7 | 5,0 | 7,00 |
| M14 x 1,5 | - | - | 10 | 7 | 5,0 | 8,10 |
| M16 x 1,5 | - | - | 10 | 8 | 5,0 | 11,0 |
| - | - | R 3/8 | 10 | 8 | 5,0 | 12,2 |
| M18 x 1,5 | - | - | 10 | 8 | 5,0 | 14,6 |
| M20 x 1,5 | - | - | 10 | 10 | 5,0 | 17,6 |
| - | - | R 1/2 | 10 | 10 | 5,0 | 19,0 |
| M22 x 1,5 | - | - | 10 | 10 | 5,0 | 22,0 |
| M24 x 1,5 | - | - | 12 | 12 | 6,0 | 30,8 |
| M26 x 1,5 | - | - | 12 | 12 | 6,0 | 38,6 |
| - | M27 x 2 | R 3/4 | 12 | 12 | 6,0 | 40,2 |
| M30 x 1,5 | M30 x 2 | - | 12 | 17 | 6,0 | 44,0 |
| - | M33 x 2 | R 1 | 12 | 17 | 6,0 | 57,5 |
| M36 x 1,5 | M36 x 2 | - | 15 | 19 | 7,5 | 85,2 |
| M38 x 1,5 | - | - | 15 | 19 | 7,5 | 94,4 |
| - | M39 x 2 | - | 15 | 19 | 7,5 | 103,0 |
| M42 x 1,5 | M42 x 2 | R 1 1/4 | 18 | 22 | 11,5 | 135,0 |
| M45 x 1,5 | M45 x 2 | - | 18 | 22 | 11,5 | 167,0 |
| M48 x 1,5 | M48 x 2 | R 1 1/2 | 20 | 24 | 11,5 | 214,0 |
| M52 x 1,5 | M52 x 2 | - | 20 | 24 | 11,5 | 253,0 |
| - | M56 x 2 | - | 22 | 32 | 13,0 | 274,0 |
| - | M60 x 2 | - | 22 | 32 | 13,0 | 350,0 |