



BSPT E NPTF

Tappi conici con esagono incassato, filettature BSPT (gas conica) e NPTF.

Dati espressi in millimetri (mm)

d	b	s	t	Peso
Filettatura BSPT (gas conica)				
UNI ISO 7/1	js16		min.	kg per 1000 pezzi (7,85 kg/dm ³)
R 1/8	9,5	4,76 (3/16")	5,0	3,9
R 1/4	12,7	6,35 (1/4")	6,5	9,5
R 3/8	14,3	7,94 (5/16")	7,0	18
R 1/2	17,5	9,52 (3/8")	9,0	35,2
R 5/8	19	12,7 (1/2")	9,5	44
R 3/4	20,7	14,29 (9/16")	9,5	66
R 1	25,4	15,87 (5/8")	12	121,5
R 1 1/4	31,7	19,05 (3/4")	14	257
R 1 1/2	31,7	19,05 (3/4")	14	350

Dati espressi in millimetri (mm)

d	b	s	t	Peso
Filettatura NPTF Dryseal				
conicità 6,25%	js16		min.	kg per 1000 pezzi (7,85 kg/dm ³)
1/16" - 27	8	3,97 (5/32")	4,0	2,0
1/8" - 27	8	4,76 (3/16")	4,0	3,5
1/4" - 18	11,1	6,35 (1/4")	5,5	7,6
3/8" - 18	12,7	7,94 (5/16")	6,5	17
1/2" - 14	14,3	9,52 (3/8")	8	26
3/4" - 14	15,9	14,29 (9/16")	8	49
1" - 11,5	19	15,87 (5/8")	9,5	93
1 1/4" - 11,5	20,6	19,05 (3/4")	11	165
1 1/2" - 11,5	20,6	25,4 (1")	11	204
2" - 11,5	22,2	25,4 (1")	11	410

Dati espressi in millimetri (mm)

<i>d</i>	<i>b</i>	<i>s</i>	<i>t</i>	Peso
Filettatura NPTF Levlseal				
conicità 7,25%	js16		min.	kg per 1000 pezzi (7,85 kg/dm ³)
1/16" - 27	6,2	3,97 (5/32")	4,0	1,5
1/8" - 27	6,2	4,76 (3/16")	4,0	2,5
1/4" - 18	10,1	6,35 (1/4")	5,5	6,3
3/8" - 18	10,1	7,94 (5/16")	6,5	13
1/2" - 14	13,5	9,52 (3/8")	8	24
3/4" - 14	13,5	14,29 (9/16")	8	40